## Specification Review Checklist

## SFB Roofing Performance Specification Type:

## **CLAY TILE**

07 32 13

This checklist can be used for new construction and building renewal grant projects

Project:		
	Revised 12/2	29/20

Checked	Specification	Paragraph	Comments	Field Acceptance
	SFB recommendation	This checklist refers to the SFB General Roofing Specification 07 30 00 numerous times which needs to be followed.		•
	General Roofing Performance Specification Para. 2.1.4.1	The Architect shall provide to the SFB at the first kickoff meeting or pre-design meeting the SFB Performance Specifications which will be used as a guideline to supplement the Architect's roofing specification before proceeding with their design. Performance Specification	Optional: Use the SFB NC kickoff meeting agenda form for BRG pre-design award meeting with the District's representatives.	
	General Roofing Performance Specification Para. 2.1.9	Has the Architect signed their Shop Drawing review stamp?		
	General Roofing Performance Specification Para. 1.2	Has a roof assessment been performed? If so, who performed this? If an assessment by the District has not been performed by others, has this Project's Architect or SFB Liaison performed their assessment in the field prior to the start of design?		
	General Roofing Performance Specification Para. 1.2.6.2	Has a pre-design award meeting with the Assessor, Project Architect, District & the SFB been held to define a direction for a scope of work?	Optional: Use the SFB NC kickoff meeting agenda form for BRG pre-design award meeting with the District's representatives.	
	General Roofing Performance Specification Para. 1.3.1	Has the Assessor provided a schedule for this project within 5 days of their notice to proceed?		
	SFB recommendation	Has the Architect or Liaison verified the existing condition? If so, can a repair or restoration be applied to extend this roof another 3-5 years?		

1 revised 29dec20 Clay Tile 07 32 13

SFB recommendation	Has the Architect or Liaison verified the interior existing finishes showing signs of water intrusion from the roof?	
General Roofing Performance Specification Para. 8	Has a Structural Engineer reviewed the as found condition & scope of work prior to the start of design?	
SFB recommendation	Has a Mechanical Engineer reviewed the as found condition & scope of work prior to the start of design?	
General Roofing Performance Specification Para. 12	The manufacturer cannot be specified in the District's IFB	
General Roofing Performance Specification Para. 2.2.1	If the project requires multiple site visits within a week, this situation shall be reported to the SFB. One visit per week is required.	
General Roofing Performance Specification Para. 2.4.1	All weekly reports by the bidder's foreman or local manufacturer representative must be submitted to the Architect and the SFB. If the manufacturer's local representative is not available, a 3 <sup>rd</sup> party QA/QC representative may be provided by the manufacturer.	Has the manufacturer been copied on these reports?
General Roofing Performance Specification Para. 3.1.1.1	The SFB shall discuss with the Registrar of Contractors open & resolved actions with the Architect as part of the contractor's qualifications prior to award of contract.	
General Roofing Performance Specification Para. 6.2	The Architect shall provide written justification for a roof replacement or restoration in lieu of repair	
General Roofing Performance Specification Para. 9.1.	All new roof installations require compliance to the minimum R/Cl values found in IECC.	
General Roofing Performance Specification Para. 10.3.2	Has the existing HVAC curb heights been verified? Are taller curbs required?	
General Roofing Performance Specification Para. 2.1.1-2.1.7	A roof shall be determined as failed when any of the following conditions exists: loss of surface granules, visible fibers/felts, curling edges, hips & ridges leaking & failed underlayment.	
SFB recommendation	Has the Architect included the assessed deficiencies in their design package?	
SFB recommendation	Are there existing solar panels on the roof? Please refer to SFB Rooftop Solar Policy	
Clay Tile SPECIFICATION 6.1.1.1-6.1.1.5.	Clay tiles shall meet the ASTM's found herein. ASTM Class A fire rating, ASTM wind resistance of 90 MPH minimum and meet the IECC solar reflectance index (SRI) for the roof pitch and material.	SFB is going to install this type of roofing system only on the <i>Historic Buildings</i> due to the aesthetics and thus, this specification 07 32 13
	ravisad 20dac20	Clay Tile 07 22 12

		can only be used as a reference document for the Design Phase. Changes need to be discussed with SFB Staff on a project-by-project basis.
Clay Tile SPECIFICATION 6.4	All fascia / barge boards to be protected from the environment in a manner by drip edge metal flashing that will provide a minimum 20-year performance and shall be sealed to prevent moisture penetration into any enclosed space at the eaves and soffits.	
Clay Tile SPECIFICATION 10.1	The minimum expectant life for a clay tile roof is 20 years	
Clay Tile SPECIFICATION 7.1.	A 2 year minimum material & labor warranty shall be provided by the Contractor.	
Clay Tile SPECIFICATION 6.1.2	Underlayment shall meet the ASTM's found in this section	
Pre-construction	Has the Architect's 6.1.2. Underlayment shall meet: design package been submitted to the District, Liaison and the Structural & Mechanical Engineers?	
Pre-construction	Has this design package been reviewed by the Structural and Mechanical Engineers?	
Pre-construction	Has the Architect's roof field observation been submitted to the Liaison?	
Bid process	Has the District's procurement department received the approved design drawings and specifications?	
Bid process	Has the District advertised these documents?	
Bid process	Is the Liaison part of this procurement selection process?	
Bid process	The District shall include the requirement of payment & performance bonds.	
General Roofing Performance Specification Para. 2.1.7	Has the manufacturer's wind load calculations been included in the Bid documents?	
Pre-construction	If any manufacturer misses out on the Pre-bid meeting, it's the bidder's responsibility to make sure the manufacturer visits the site so a warrant document can be provided with the bid.	

3 revised 29dec20 Clay Tile 07 32 13

DISTRICT NAME	DISTRICT ACKNOWLEDGED DA	TE
SFB LIAISON NAME	SFB LIAISON ACKNOWLEDGED	DATE
ARCHITECT NAME	ARCHITECT ACKNOWLEDGED	 DATE